

Hy-Lok USA, Inc.


14211 Westfair West Dr.

Houston, TX 77041, USA

Phone: 832.634.2000 • Fax: 832-634-2099

Email: info@hylokusa.com

Q Series Female Pipe Thread Stem Connector Fittings



Results 1 - 16 of 16

Part Number	Flow Coefficient (Cv)	Length (L)	Width Across Flat (H)	Working Pressure	Temperature Rating with FKM O-Ring
Q1SSF-2N	0.3	2.01 in 51.1 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1SSF-4N	0.3	2.26 in 57.4 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSF-4N	0.9	2.35 in 59.7 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSF-6N	0.8	2.35 in 59.7 mm	7/8 in 22.2 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3SSF-8N	2.0	2.82 in 71.6 mm	1 1/16 in 26.9 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1SSF-4R	0.3	2.26 in 57.4 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSF-6R	0.8	2.35 in 59.7 mm	7/8 in 22.2 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3SSF-8R	2.0	2.82 in 71.6 mm	1 1/16 in 26.9 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSF-2N	0.2	2.07 in 52.6 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSF-4N	0.2	2.32 in 58.9 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSF-4N	0.5	2.47 in 62.7 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSF-6N	0.5	2.47 in 62.7 mm	7/8 in 22.2 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3DSF-8N	1.3	3.02 in 76.7 mm	1 1/16 in 26.9 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSF-4R	0.2	2.32 in 58.9 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSF-6R	0.5	2.47 in 62.7 mm	7/8 in 22.2 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3DSF-8R	1.3	3.02 in 76.7 mm	1 1/16 in 26.9 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F

Results 1 - 16 of 16