

Hy-Lok USA, Inc.


14211 Westfair West Dr.

Houston, TX 77041, USA

Phone: 832.634.2000 • Fax: 832-634-2099

Email: info@hylokusa.com

Q Series Hy-Lok Tube Stem Connector Fittings



Results 1 - 14 of 14

Part Number	Flow Coefficient (Cv)	Length (L)	Width Across Flat (H)	Working Pressure	Temperature Rating with FKM O-Ring
Q1SSH-2T	0.08	2.32 in 58.9 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1SSH-4T	0.3	2.36 in 59.9 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSH-6T	1.0	2.52 in 64.0 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3SSH-8T	2.4	2.96 in 75.2 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1SSH-6M	0.3	2.36 in 59.9 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSH-10M	1.0	2.65 in 67.3 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3SSH-12M	2.4	2.96 in 75.2 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSH-2T	0.08	2.77 in 60.4 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSH-4T	0.2	2.42 in 61.5 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSH-6T	0.5	2.64 in 67.1 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3DSH-8T	1.5	3.16 in 80.3 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSH-6M	0.2	2.42 in 61.5 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSH-10M	0.5	2.79 in 70.4 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3DSH-12M	1.5	3.16 in 80.3 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F

Results 1 - 14 of 14