

Hy-Lok USA, Inc.


14211 Westfair West Dr.

Houston, TX 77041, USA

Phone: 832.634.2000 • Fax: 832-634-2099

Email: info@hylokusa.com

## Q Series Male Pipe Thread Stem Connector Fittings



Results 1 - 16 of 16

Part Number	Flow Coefficient (Cv)	Length (L)	Width Across Flat (H)	Working Pressure	Temperature Rating with FKM O-Ring
Q1SSM-2N	0.3	2.07 in 52.6 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1SSM-4N	0.3	2.22 in 56.4 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSM-4N	0.9	2.32 in 58.9 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSM-6N	0.8	2.35 in 59.7 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3SSM-8N	2.0	2.84 in 72.1 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1SSM-4R	0.3	2.22 in 56.4 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2SSM-6R	0.8	2.35 in 59.7 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3SSM-8R	2.0	2.84 in 72.1 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSM-2N	0.2	2.13 in 54.1 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSM-4N	0.2	2.28 in 57.9 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSM-4N	0.5	2.44 in 61.9 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSM-6N	0.5	2.47 in 62.7 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3DSM-8N	1.3	3.04 in 77.2 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q1DSM-4R	0.2	2.28 in 57.9 mm	5/8 in 15.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q2DSM-6R	0.5	2.47 in 62.7 mm	3/4 in 19.1 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F
Q3DSM-8R	1.3	3.04 in 77.2 mm	15/16 in 23.8 mm	Up to 3000 psig Up to 206 bar	-23 ~ 204 °C -10 ~ 400 °F

Results 1 - 16 of 16